



15-06 Morlot Avenue, Fair Lawn, NJ 07410 USA Tel: (201) 796-2690 Fax: (201) 796-8818

info@articulight.com

articulight@aol.com

www.articulight.com

LED SERIES

COLOR BLOCK 318



FEATURES AND SPECIFICATIONS

Field angle: 34° x 23°
Beam angle: 18° x 15°
Foot candles: 675 @ 1 meter
Lux: 7,270 @ 1 meter
Light Source: 54 (18 red, 18 green, 18 blue) 1W LEDs 100,000 hours
Current draw: (peak 84W @ 120V) (inrush 42W @ 120V)
Power: Switchable 110V/240V 50/60Hz
Weight: 18 lbs (8.2kgs)
Size: 22.5 in x 7.5 in x 8.3 in
570mm x 190mm x 210mm
12-channel DMX-512 LED bank system (with ID addressing) divided into 3 cells each with 4 channels
Separate DMX channels for red, green, blue, cyan, magenta, yellow and white
Blackout/static/dimmer/strobe
Separate RGB control over each individual pod
RGB color mixing with without DMX controller
Durable and weather resistant, IP 65 rated
Indoor / Outdoor LED Wash
Flip-down knobs to interlock multiple units, which can create blinder, wall and strip light effects (flush mounted)
Automatic DMX-512 addressing (ADAS)
Built-in automated programs via dedicated or DMX controller
LED display with lock-out feature
Black anti-UV plastic cover
Low power consumption
Optional diffusion lens



Dedicated Controller
4- channel DMX-512 Controller
Controls up to 66 COLOR BLOCK 318TM (using ID addressing)
16 editable programs
- 8 color wash
- 8 color changing
8 programmable shows each with 100 steps
Full RGB color mixing
Control of each pod
Playback schedules via internal clock
Digital LCD display with password protection
Power : DC12V 500mA 110V or 230V
Weight : 1 lb (.5 kg)
Dimensions: 22.5in x 7.5in x 8.3in (178mm x 127mm x 51mm)

DUE TO CONTINUOUS IMPROVEMENTS, SPECIFICATIONS ARE SUBJECT TO
CHANGE WITHOUT PRIOR NOTICE