

ARTICULIGHT

15-06 Morlot Avenue, Fair Lawn, NJ 07410 USA Tel: (201) 796-2690 Fax: (201) 796-8818

info@articulight.com

articulight@aol.com

www.articulight.com

SEARCH LIGHTS

TRACER MK2 4000 TRACER HTI 4000 Multibeam Outdoor Searchlight



Fitted with an HMI 4000W discharge lamp, this powerful multi-beam sky tracker projects 15 beams visible from an outstanding distance, for a 28 degrees beam aperture. Performance depends on ambient light and atmospheric conditions. The latest development features control via standard DMX 512 signal, for a total of 4 channels, allowing accurate selection of preset beam rotation speed, scanning amplitude and scanning speed, as well as strobe and blackout functions. Housing is weatherproofed with IP 23 rating. Head and mount detachable from the base. Lamp timer incorporated as power factor correction system. Power supply 380V. A new model is now available, fitted with an HTI 4000W discharge lamp, which benefits of a shorter arc, giving even brighter light emission. Power supply 230-240V. Tracer HTI features head, mount and base as a single assembly for a more compact size.

TECHNICAL DATA

LAMP: HMI or HTI, 4000w, G38 base for HMI and S25.5 for HTI, 500 hour, 240,000 lumens, 6,000 degrees Kelvin color temperature

ANGLE: 28 degrees

DIMMER: Mechanical blackout only.

STROBE: 1 FPS

DMX CHANNELS: 4

STAND ALONE: Yes

MASTER/SLAVE: Yes

ONBOARD CONTROL: Yes

PAN: 180 degrees

IP RATING: 23

COOLING: Forced ventilation

DIMENSIONS: Height: 1220mm (HMI), 1110mm (HTI)

Width: 750mm (HMI), 750mm (HTI)

Depth: 580mm (HMI), 550mm (HTI)

POWER: 380v (HMI), 230-240v (HTI), 50-60 HZ, 11Amp (HMI), 28 Amp (HTI)

MODELS: GR0038 TRACER MK2 HMI 4000W

GR0033 TRACER HTI 4000W

DUE TO CONTINUOUS IMPROVEMENTS, SPECIFICATIONS MAY CHANGE WITHOUT PRIOR NOTICE.